

Modello	TK3000/H	TK6000/H	TK9000/H	TK5K	TK8K	TK15K	Model
Codice	TKD#XX50CX52_ TKD#XX50HX52_	TKD#XX60CX52_ TKD#XX60HX52_	TKD#XX63CX52_ TKD#XX63HX52_	TKE#XX70HX52S	TKE#XX80HX57S	TKE#XX90HX57S	Code
Volume refrigerato (lt)	3000	6000	9000	-			Refrigerated volume (lt)
Temperatura d'impiego	25°C						Operating temperature
Alimentazione	230V 50Hz			380-415V 50Hz 3ph			Supply
Potenza frigorifera (in raffreddamento)	2200 W **	2800 W *	3300 W *	5,8 KW *	8,7 KW *	14,6 KW *	Cooling capacity (cooling)
Potenza elettrica (in raffreddamento)	750 W **	900 W *	1200 W *	2030 W *	4350 W *	6890 W *	Power consumption (cooling)
Potenza elettrica (in riscaldamento)	800 W **	1200 W *	1200 W *	1500 W **	2800 KW **	4100 W **	Power consumption (heating)
Refrigerante	R410a	R410a	R410a	R410a	R410a	R410a	Refrigerant
Temperatura ambiente	+5° / +38 °C						Ambient temperature
Temperatura acqua	+5° / +30 °C						Water temperature
Dimensioni (mm)	395x600x565(h)			816x690x835(h)	816x690x850 (h)	816x690x1050 (h)	Dimensions (mm)
Peso (kg)	39	40	47	79	105	130	Weight (kg)

* Reported value refers to the following condition: room temperature 30°C, water temperature 25°C

** Reported value refers to the following condition: room temperature 5°C, water temperature 25°C